



# PE.SEB SS.PE.SEB

METRIC THREADS

## FALL PROTECTION ANCHORAGE POINT



Reference	Diameter	Number of persons		Standard L <sub>1</sub> (mm)	Torque (Nm)		S (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Weight	
		EN 795:2012	CEN/TS 16415:2013									(kg)	(lbs)
PE.SEB M 12	M 12 (x1,75)	1 pers.	2 pers.	21	15	20	6	30	34	60	57	0,24	0.53
PE.SEB M 16	M 16 (x2)	1 pers.	2 pers.	27	50	35	8	38	45	88	80	0,80	1.76
PE.SEB M 20	M 20 (x2,5)	1 pers.	2 pers.	30	100	35	8	38	45	88	80	0,80	1.76



Reference	Diameter	Number of persons		Standard L <sub>1</sub> (mm)	Torque (Nm)		S (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Weight	
		EN 795:2012	CEN/TS 16415:2013									(kg)	(lbs)
SS.PE.SEB M 12	M 12 (x1,75)	1 pers.	2 pers.	21	15	35	8	38	45	90	80	0,80	1.76
SS.PE.SEB M 16	M 16 (x2)	1 pers.	2 pers.	27	50	35	8	38	45	90	80	0,82	1.81
SS.PE.SEB M 20	M 20 (x2,5)	1 pers.	2 pers.	30	100	35	8	38	45	90	80	0,84	1.85
SS.PE.SEB M 24	M 24 (x3)	1 pers.	2 pers.	36	150	35	8	38	45	90	80	0,90	1.98

11.2024

78